
Mounting system for your «glass composition» Type

В

Congratulations with your just required unique glass object. Please read text and explanation below for a smooth mounting in order to enjoy for many years your new color-composition .Please maintain only with a moisturized cloth and use no aggressive detergent .



in case of any questions mail to: pvstudio@hetnet.nl

We recommend to place a blanket or other soft material on the ground to place the object on during the installation. Also leave the protection corners on until final hanging is achieved.


Required tools:

measurer, spirit-level, 6 mm stone drill bit, drilling machine and a Phillips-head screwdriver.


Attention; Type of wall: a. Stone- or concrete walls: Use supplied fixing materials.

- b. Plasterboard walls: Require additional special fixing plugs («Driva or Fischer») to fit the supplied screw sizes/dimensions.
- c. Ytong or Gypsum walls: Use metal drill bits instead of stone bits, attach with the supplied plugs and screws.
- d. Wooden walls: Use supplied screws for fixing without plugs.


Please check if there are no water.gas or electricity pipes in the selected drill- positions.




Mark position on wall, to avoid damages: leave corner protectors on.




Position and mark drill positions for top end as indicated. Find X by inserting hooks into mountinplates on Object and measure rhe centers.




You can also measure your object and mark corners directly onto the wall.




Drill 6 mm holes -35 mm deep- and fix mounting plates (with washer on the outside) with plugs and screws.




Make sure potential top line of your object is leveled.




Check if leveled ,otherwise adjust one.







Mark position of bottom-end on wall, to avoid damages leave cornerprotectors on.




Drill 6 mm hole 30 mm deep and fix with plugs and screws with small round button facing the wall.




Before you take off Object from wall check if leveled otherwise adjust (see F.)



Remove protecting paper and aline button.



Mark drill Position for bottom fixing as indicated.



Hang object and push firmly at bottom end to attach bottom fixings to your object.

In case you would like to remove or replace: Pull at the bottom end to release the fixing buttons and lift object to unhook at the top.

The round but-tons at bottom end will stay on the wall and the square plates will sit on the object. At re-installing just hang in and click bottom end into buttons.

Also please be aware this is a unique piece all hand-cut and made so slight imperfections just indicate you have a genuine artifact at hand.

In case of any additional questions please **contact** us by e-mail .